

Smart Winder - MP - 01



Description

The model – *Optima MP01* is specially designed to address the specific application of providing varying pitch in a single program at low capital and running cost through a simple design & construction.

Menu-driven programming through alpha-numeric dialogue display, a powerful set of programmable parameters and multi-program memory help in realizing complex winding programs with exceptional ease.

Technical Specifications

Particulars	Specifications
Spindle	Single (Side Loading)
Spindle Speed	300 - 700 RPM
Wire Diameter	0.1 mm to 0.3 mm
No. of Programs	99 (max.)
No. of Steps /Programs	9 (max.)
Winding Width	90 mm (max.)
Power Requirements	220 V AC, 50/60 Hz,
Dimensions (mm)	400 (L) x 200 (W) x 320 (H) [With Accessories]
Weight	30 Kgs. (approx.)

Standard Accessories

- Tensioner mounting stand and spool container for single spindle
- Wire guide mounting for single spindle
- Tailstock for 1100
- Nozzle and nozzle block
- Ball screw rod
- De Reeler - friction type

Application

- Varying pitch coils
- Fuel gauge
- Fuel tank
- Potentiometer

Synthesis Winding Technologies Pvt. Ltd.



H.O. & Works :

#14/A, Shanthipura Road, Electronic City, Phase II
BANGALORE-560 100. INDIA.
Phone: +91-80-30282020/35/36
E-mail: marketing@synthesis-winding.com
www.synthesis-winding.com

Regional Office (West) :

#12, Symphony C, Range Hills Road
(Off Ganesh Kind Road),
PUNE - 411 020. Maharashtra.
Phone: +91-20-25560661
E-mail: marketing@synthesis-winding.com

Regional Office (North India) :

UG-11, Ansal Imperial Tower, C-Block
Naraina Vihar, Community Centre
NEW DELHI - 110 028.
Phone: +91-11-41530848
E-mail: marketing@synthesis-winding.com